

13-14 SERIES LIGHT MEDIUM DUTY CASTERS



- FEATURES:**
- Finish – Bright Zinc plating
 - Swivel – Double ball bearing with hardened raceways for extra strength
 - Construction – Heavy gauge cold rolled steel, formed for strength
 - Axle – 5/16" diameter bolt with lock nut
 - Optional – Bright nickel plating fork and upper race add 5 to series number example: Change 13 series to 135 series or, 14 series to 145 series
 - Optional Accessories

**SERIES 13
STANDARD STEMS**

3/8-16 x 1 1/2" 1/2-13 x 1"
7/16-14 x 1 1/2" 1/2-13 x 1 1/2"
1/2-13 x 2 3/4"

**SERIES 14
Standard cold headed stem sizes:**

7/16" x 1 3/8" • 7/16" x 1 15/16"
Machined stems available from
1/2" dia. to 1" dia.

Square stems available with drilled hole:
.845" • .860" • .875"

WHEEL				CAPACITY	LOAD HEIGHT	SWIVEL RADIUS	CASTER ORDERING NUMBER		APP. WEIGHT
DIAMETER	TREAD WIDTH	TYPE	BEARING	POUNDS	INCHES	INCHES	SERIES 13	SERIES 14	POUNDS
3	15/16	Soft Tread Rubber	Delrin	100	3 5/8	2 3/4	3-13-103	3-14-103	1 1/8
		Hard Tread Rubber	Delrin	125			3-13-104	3-14-104 3	
		Soft Tread Rubber	Delrin	100			3-13-433G	3-14-433G	
	1 1/8	Polyolefin	Plain	125			3-13-511	3-14-511	
4	15/16	Soft Tread Rubber	Delrin	115	4 5/8	3 5/16	4-13-103	4-14-103	1 1/2
		Hard Tread Rubber	Delrin	140			4-13-104	4-14-104	
		Soft Tread Donut	Delrin	115			4-13-433	4-14-433	
	1	Polyolefin	Plain	150			4-13-511	4-14-511	
		Poly Loc Grey	Delrin	150			4-13-211G	4-14-211G	
		Poly Loc Grey	Ball	150			4-13-212G	4-14-212G	
		Poly Loc Poly	Ball	150			4-13-212P	4-14-212P	
5	1 1/4	Soft Tread Rubber	Delrin	125	5 5/8	4	5-13-103	5-14-103	1 7/8
		Hard Tread Rubber	Delrin	150			5-13-104	5-14-104	
		Soft Tread Donut	Delrin	125			5-13-433	5-14-433	
	1	Polyolefin	Plain	150			5-13-511	5-14-511	
		Poly Loc Grey	Delrin	160			5-13-211G	5-14-211G	
		Poly Loc Grey	Ball	160			5-13-212G	5-14-212G	
		Poly Loc Poly	Ball	160			5-13-212P	5-14-212P	