

134-136 SERIES MEDIUM DUTY



SERIES 134



SERIES 136

**SERIES 134
Standard Spring Ring Stems**

- 3/4" dia. x 23/16"
- 13/16" dia. x 23/16"
- .845 dia. x 23/16"
- .865 dia. x 23/16"
- 1" dia. x 23/16"
- .860 square x 23/16"

**SERIES 136
Standard Threaded Stems**

- 1/2-13 x 3/4" 1/2-20 x 2 1/4"
- 1/2-13 x 1" 5/8-11 x 1 1/4"
- 1/2-13 x 1 1/2" 5/8-18 x 1 3/4"
- 1/2-20 x 3/4" 3/4-10 x 1"

Note: Many other stem sizes are available on request. Contact the factory for more information.

WHEEL				CAPACITY	LOAD HEIGHT	SWIVEL RADIUS	CASTER ORDERING NUMBER			
DIAMETER	TREAD WIDTH	TYPE	BEARING	POUNDS	INCHES	INCHES	SERIES 130	SERIES 131	SERIES 134	SERIES 136
5	1 1/2"	Advantage Rubber	Roller	400	6 1/4	4	5-130-215GF	5-131-215GF	5-134-215GF	5-136-215GF
		Poly Loc Grey	Roller	400			5-130-215G	5-131-215G	5-131-215G	5-136-215G
		Poly Loc Poly	Roller	400			5-130-215P	5-131-215P	5-134-215P	5-136-215P
6	1 1/2"	Phenolic	Plain	400	7 1/2	4 3/4	6-130-121	6-131-121	6-134-121	6-136-121
		Phenolic	Roller	400			6-130-221	6-131-221	6-134-221	6-136-221
		Polyolefin	Delrin	400			6-130-523	6-131-523	6-134-523	6-136-523
		Polyolefin	Roller	400			6-130-525	6-131-525	6-134-525	6-136-525
		Advantage Rubber	Roller	400			6-130-215GF	6-131-215GF	6-134-215GF	6-136-215GF
		Poly Loc Grey	Roller	400			6-130-215G	6-131-215G	6-134-215G	6-136-215G
		Poly Loc Poly	Roller	400			6-130-215P	6-131-215P	6-134-215P	6-136-215P
8	1 1/2"	Advantage Rubber	Roller	250	9 1/2	6 1/2	8-130-215GF	8-131-215GF	8-134-215GF	8-136-215GF
		Poly Loc Grey	Roller	250			8-130-215G	8-131-215G	8-134-215G	8-136-215G
		Poly Loc Grey	Roller	250			8-130-215P	8-131-215P	8-134-215P	8-136-215P
		Polyolefin	Delrin	250			8-130-523	8-131-523	8-134-523	8-136-523
		Polyolefin	Roller	250			8-130-525	8-131-525	8-134-525	8-136-525
		Semi Pneumatic	Ball	150			8-130-920	8-131-920	8-134-920	8-136-920

* For stem type casters, deduct 3/16" from load height