

# 25-26 SERIES LIGHT MEDIUM DUTY CASTERS



### FEATURES:

- Finish – Bright Zinc plating
- Swivel – Double ball bearing with hardened raceways for extra strength
- Construction – Heavy gauge cold rolled steel, formed for strength
- Axle – 5/16" diameter bolt with lock nut
- Optional – Bright nickel plating fork and upper race add 5 to series number example: Change 25 series to 255 series or, 26 series to 265 series
- Optional Accessories

### SERIES 25

NOTE: Please add proper suffix number for top plate size desired from chart.

### SERIES 26

NOTE: Rigid casters supplied only with top plate options 3 & 4.

### STANDARD TOP PLATE SIZES

SUFFIX NO.	OVERALL SIZE	BOLT HOLE SPACING	BOLT HOLE SIZE
1	2 7/16 x 2 7/16	1 3/4 x 1 3/4	1/4
2	1 3/4 x 3	1 x 2 1/4	1/4
3	2 3/8 x 3 5/8	1 3/4 x 3	1/4
4	2 3/8 x 3 5/8	1 3/4 x 3	5/16

WHEEL				CAPACITY	LOAD HEIGHT	SWIVEL RADIUS	CASTER ORDERING NUMBER		APP. WEIGHT
DIAMETER	TREAD WIDTH	TYPE	BEARING	POUNDS	INCHES	INCHES	SERIES 25	SERIES 26	POUNDS
3	15/16	Soft Tread Rubber	Delrin	100	3 3/4	2 3/4	3-25-103	3-26-103	1 1/8
		Hard Tread Rubber	Delrin	125			3-25-104	3-26-104	
		Soft Tread Rubber	Delrin	100			3-25-433G	3-26-433G	
	1 1/8	Polyolefin	Plain	125			3-25-511	3-26-511	
4	15/16	Soft Tread Rubber	Delrin	115	4 3/4	3 5/16	4-25-103	4-26-103	1 1/2
		Hard Tread Rubber	Delrin	140			4-25-104	4-26-104	
		Soft Tread Donut	Delrin	115			4-25-433	4-26-433	
	1	Polyolefin	Plain	150			4-25-511	4-26-511	
		Poly Loc Grey	Delrin	150			4-25-211G	4-26-211G	
		Poly Loc Grey	Ball	150			4-25-212G	4-26-212G	
		Poly Loc Poly	Ball	150			4-25-212P	4-26-212P	
5	15/16	Soft Tread Rubber	Delrin	125	5 3/4	4	5-25-103	5-26-103	1 7/8
		Hard Tread Rubber	Delrin	150			5-25-104	5-26-104	
		Soft Tread Donut	Delrin	125			5-25-433	5-26-433	
	1	Polyolefin	Plain	150			5-25-511	5-26-511	
		Poly Loc Grey	Delrin	160			5-25-211G	5-26-211G	
		Poly Loc Grey	Ball	160			5-25-212G	5-26-212G	
		Poly Loc Poly	Ball	160			5-25-212P	5-26-212P	