

50MG-54MG-56MG

FUTURA BRAKE LOCK AND SWIVEL LOCK HEALTH CARE CASTERS



5-50MG-213GP APSL

When you want to enhance appearance and provide maintenance-free equipment to your customer, specify brand new FUTURA casters for all your designs. These casters outperform everything else in their class - they're smooth, quiet, attractive, and super-tough all at once.

FUTURA casters represent the future of caster technology for the most demanding institutional uses; they have the aesthetics expected by high-end cart designers, and the performance and value needed to put these casters into the broadest range of applications.

- Total locks are available - locks swivel and wheel simultaneously; also available with single position directional lock for straight tracking
- Available with tough Jarvis **Poly-Loc** polyurethane or **Advantage** TPR wheels for smooth, super quiet operation
- Ultra-low maintenance
- Great aesthetics with attractive optional thread guards and axle caps available on standard casters

WHEEL				CAPACITY POUNDS	LOAD HEIGHT INCHES	SWIVEL RADIUS INCHES	TOP PLATE CASTER ORDERING NUMBER		
DIAMETER	TREAD WIDTH	TYPE	BEARING				PLAIN	TOTAL LOCK	SWIVEL LOCK
5	1 1/4	Advantage Round	Delrin	250	6 3/8	4 plain	5-50MG-314GD	5-50MG-314GD APSL	5-50MG-314GD SLI
		Advantage Flat	Delrin				5-50MG-314GF	5-50MG-314GF APSL	5-50MG-314GF SLI
		Polyurethane Delrin	Plain				5-50MG-314GP	5-50MG-314GP APSL	5-50MG-314GP SLI
		Advantage Round	Ball			5 w/lock or brake	5-50MG-213GD	5-50MG-213GD APSL	5-50MG-213GD SLI
		Advantage Flat	Ball				5-50MG-213GF	5-50MG-213GF APSL	5-50MG-213GF SLI
		Polyurethane	Ball				5-50MG-213GP	5-50MG-213GP APSL	5-50MG-213GP SLI

**Standard top plate: 23/8 x 35/8 with 13/4 x 3 bolt hole spacing for 5/16 bolt; for other options contact the factory*

To order optional thread guards, add suffix TG.

To order axle caps on standard casters, add suffix A

STEM CASTERS To order any stem caster, change the series number 50MG to 54MG or 56MG and specify the desired stem.

STANDARD STEM SIZES	
SPRING RING MOUNT 54Mg	THREADED MOUNT 56Mg
.845" dia. x 23/16	1/2-13 x 1"
.865" dia. x 23/16	
.860" sq. x 23/16	1/2-13 x 11/2"

Other size options are available - please contact the factory for further information.

