


SERIES S30, S31, S32, S34, S36 AND S40

Stainless Steel

5-S30-314GD-2
Standard Top Plate
 2 3/8" x 3 5/8" with
 1 3/4" x 3" bolt hole



SERIES S30

S-532-121
Standard Stem
 3/4" round x 2
 w/three drill holes



SERIES S32

5-S36-113P
Standard Stem
 1/2-13 x 1 1/2"



SERIES S36

5-S31-113P
Standard Top Plate
 2 3/8" x 3 5/8" with
 1 3/4" x 3" bolt hole



SERIES S31

5-S34-105N
Standard Stem
 .845" x 2 3/16"
 spring ring



SERIES S34

5-S40-213G
Standard Stem
 No. 11 appl.
 No. 19A appl.



SERIES S40

We offer this medium duty stainless steel caster series with top plates and stems. The top plate and stems listed are stainless steel. Stainless steel brakes are available on all swivel series and one position stainless steel swivel locks are available on top plate casters.

WHEEL				CAPACITY	LOAD HEIGHT	SWIVEL RADIUS	CASTER ORDERING NUMBER		APP. WEIGHT
DIAMETER	TREAD WIDTH	TYPE	BEARING	POUNDS	INCHES	INCHES	SERIES S 30 SWIVEL PLATE	SERIES S 31 SWIVEL PLATE	POUNDS
4	1 1/4"	Neoprene	Delrin	180	5 1/16	3 1/2	4-S30-105N	6-S30-121	2 1/4
		Advantage Donut	Delrin	250			4-S30-314GD	4-S31-314GD	
		Advantage Flat	Delrin	300			4-S30-314GF	4-S31-314GF	
		Polyolefin	S.S. Sleeve	300			4-S30-513	4-S31-513	
		Poly Loc Grey	Delrin	300			4-S30-314G	4-S31-314G	
	1 1/2"	Phenolic	S.S. Sleeve	300			4-S30-121	4-S31-121	
5	1 1/4"	Neoprene	Delrin	200	6 1/8	4	5-S30-105N	5-S31-105N	2 3/4
		Advantage Donut	Delrin	250			5-S30-314GD	5-S31-314GD	
		Advantage Flat	Delrin	300			5-S30-314GF	5-S31-314GF	
		Polyolefin	S.S. Sleeve	300			5-S30-513	5-S31-513	
		Polyurethane	S.S. Ball	300			5-S30-113P	5-S31-113P	
		Poly Loc Grey	Delrin	300			5-S30-314G	5-S31-314G	
	1 1/2"	Phenolic	S.S. Sleeve	300			5-S30-121	5-S31-121	
6	1 1/4"	Neoprene	Delrin	220	7 3/16	4 1/2	6-S30-105N	6-S31-105N	3 1/4
		Advantage Donut	Delrin	300			6-S30-314GD	6-S31-314GD	
		Polyolefin	S.S. Sleeve	300			6-S30-521	6-S31-521	
		Poly Loc Grey	S.S. Ball	300			6-S30-213G	6-S31-213G	
		Poly Loc Grey	Delrin	300			6-S30-314G	6-S31-314G	
	1 1/2"	Phenolic	S.S. Sleeve	300			6-S30-121	6-S31-121	

Note: To order any stem caster shown above, change the caster ordering number to the series number desired. Be sure to specify the stem size. Deduct 1/8" from load height when using a stem caster.

Example: Plate caster 5-S30-105N to threaded stem caster 5-S36-105N with 1/2-13 x 1 1/2" stem.